

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Floor and wall finishing

WST 1000 FV

Order no. 350.923



Giraffe® scrouer for walls and ceilings

- FV electronic control: constant speed, soft-start and overload protection
- Using a unique telescopic system, the Giraffe® adapts to your needs. Length adjustable from 1330 mm - 1730 mm. Open telescope lock lever, pull out handle and close lever.
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance.
- Vacuum dust collection: protects against abrasive dust, reduces disc wear, keeps concrete pores for the new coat open
- Flexible rubber vacuum ring with low-wear metal ring: moves smoothly over the surface and protects against dust and stones flying out
- Dust extraction system: with metal ring on the guard, flexible suction hose from the scouring head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX industrial vacuum cleaner, models S 36, S 47 and S 47 M
- The scrouer with universal joint shaft and the new scouring head have been purpose-coordinated. This tool quickly and easily removes burrs and other unevenness from walls and ceilings

Technical attributes	WST 1000 FV
Disc Ø	125 mm
Speed without load	8000 rpm
Power input	1010 watt
Power output	600 watt
Tool fixture	28 mm Ø
Dimensions in mm	1330-1730
Weight	5,50 kg

Standard equipment

1 Turbo grinding pad 125	349.623
1 FixTec quick-clamp nut M 14	313.459
4 m vacuum hose, 32 mm Ø with positive-lock connector and vac connection	340.782
Padded carry case	1 piece

Accessories

Diamond cup wheel



Turbo grinding pad, maximum material removal with optimum quiet running

Dimensions QTY/PKG: Order no.
in mm:

125 Ø x 28 1 349.623

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Floor and wall finishing

Dry grinding diamond cups



Thermo-Whirljet for thin coatings and lightly abrasive materials: Thermoplastic coatings, Paint, Graffiti, thin glue residues on concrete or screed, Rubber based coatings. Reduced weight with the FLEX flange. Only to be used on the FLEX long-neck renovation grinder. The grinding disc with the angular arranged diamond segments allows for a quicker work rate than with normal disc. The large dimensioned delta shaped holes in the discs causes an air vortex that removes all dust from the working surface and prevents the segments from clogging or overheating and so reducing wear. The light weight disc reduces wear on the motor. Not for use on edges.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	323.071
--------------	----------	----------------



Screed-Whirljet for abrasive materials: Abrasive screeds (with quartz sand), fresh concrete, plaster, abrasive limestone (with quartz sand) sandstone, fire clay, asphalt. Reduced weight, with FLEX special flange - only to be used on the FLEX long-neck renovation grinder. Not to be used for working on edges.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	324.361
--------------	----------	----------------



Concrete-Whirljet the grinding disc for concrete: old concrete, concrete slabs and stone - natural and artificial slabs, lime sand brick hard, paving slabs, tile glue, removing glazing from ceramic tiles. Reduced weight, with the FLEX special flange - only to be used on the FLEX long-neck renovation grinder. Not to be used on edges.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	323.063
--------------	----------	----------------

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Floor and wall finishing

Rubber extraction rings



The flexible rubber vacuum ring moves smoothly over the surface and provides optimum protection against dust and stones flying out.

Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	257.246
--------------	----------	----------------

Concrete grinder head without disc



Dimensions QTY/PKG: Order no.
in mm:

125 Ø	1	350.931
--------------	----------	----------------